



. 4/15

X SHIEMS FORD	Decibel Product:	D8882 H66	60 dea 11 d8 Gen	0.00	-	1000	
ANTENNA_POINT	Decibel Products	DB884 H45	45 dag, 15 dB Gain	80	1	0.00	000
ANTENNA_POINT	Decibel Products	DB884 HG0	60 deg. 14.3 dB Gain	. 80	-	. 00	200
ANTENNA_POINT	Decibel Products	DB 886 H60	60 deg. 15 dB Gain	8	. <u>-</u>	9	900
ANTENNA_POINT	Decibel Products	DB894H60	60 deg. 13 dBd gam panel	8	_	800	
ANTENNA_POINT	Decibel Products	DB 838H60	60 deg. 16 dB gain panel	8	_	800	2
ANTENNA POINT	Decibel Products	M-060083690	90 deg. 13.5 dBd Gain PCS -45/+45	80	,	000	2 2
ANTENNA_POINT	Decibel Products	DB974H105 1920	105 deg. 10.50 dB Gam 1920 MHz	9	-	8	
ANTENNA_POINT	Decibel Products	DB974H30	11 dBd Gam 90 deg.	8		000	8 8
ANTENNA_POINT	Decibel Products	DB978H120	120 deg. 13 dBd Gain PCS	0.00	-	8	80
ANTENNA_POINT	Decibel Products	DB978H90M	90 deg. 14 dBd Gain PCS	8	_	000	2
ANTENNA_POINT	Decibel Products	DB380H105-M	105 deg. 14.5 dBd Gain PCS	8	-	8	8 8
ANTENNA_POINT	Decibel Products	DB380H120-M	120 deg. 14 dBd Gain PCS	000		80	
ANTENNA_POINT	Decibel Products	DB380H65+M	65 deg. 16.5 dBd Gain PCS	80	_	800	8 6
ANTENNA_POINT	Decibel Products	DB380H30M	90 deg. 15 dBd Gain PCS	000		2	8 8
GANTENNA_POINT	EMS Wireless	1051000NAS	Wireless 105 dea. 9.5 dBd Gain Panel	8	. ,-	8 8	8 8
ANTENNA_POINT	EMS Wireless	601500NA	60 deg. 15.0 dBd gam panel	800		8 8	8 8
ANTENNA POINT	ш	900900NA	90 deg. 9.3 dBd gam Panel	8		8 8	8 8
ANTENNA_POINT	ш	900900NAS	90 deg. 9.5 dBd gain panel	80	_	8 8	8 6
ANTENNA_POINT	w	900910NA	90 deg. 9.5 dBd gein pemel	80	_	80	
ANTENNA_POINT	EMS Wireless	900910NAS	90 deg. 9.5 dBd gain panel	8	_	000	8 8
ANTENNA POINT	EMS Wireless	901200NA	90 deg. 12 dBd gain Panel	8	,	000	8 0
ANTENNA POINT	EMS Wireless	901200NAS	90 deg. 12.0 dBd gain Panel	0.00	_	8	000
ANTENNA POINT	EMS Wireless	901205NAS	90 deg. 12.5 dBd gain Panel	8	-	000	000
ANTENNA POINT	EMS Wireless	901210NAS	90 deg. 12.0 dBd gain Panel	80	_	000	90
KANTENNA POINT	_	901300NA	90 deg. 13.3 dBd gain Panel	0.00	-	000	8 0
NIENNA POINT	_	DV105-08-00_A2	Optifiange BdBd Vertical Polar Array	90	_	000	800
ANTENNA POINT	_	DV105-08-00_M2	OptiRenge 8dBd Vertical Poler Array	0.00	_	80	800
ANIENNA POINT	_	DV105-09-00_A2	Optifiange 9dBd Vertical Polar Array	8	_	000	00.0
ANTENNA POINT	EMS Wireless	DV105-09-00_M2	Optifil 9d8d Vertical Polar Array	80		000	000
ANTENNA POINT	EMS Wireless	DV65-10-00_A2	OptiFlange 10dBd Vertical Polar Array	80	_	8	200
		聖職等一種 できなかられた 一一を使え	の著名を含める。 1 年間の日本の名 本の本語の 一日の人の名称 (大き) 一年の人の題が	1			













Figure .

8/15






Select positions within the 3D environmental model at which specific signal-to-interference ratio, specific throughput, etc.) metric (e.g., specific received signal strength coverage level, Select positions within the 3D environmental model that are selection set of available component models and/or types Select input signal characteristics (e.g., signal power) for a particular wireless communication system performance Specify whether to allow all possible configurations for suitable for the placement of communication equipment Select set of component models and/or types from a selected component models and/or component types selected component models and/or component types is desired. Selected positions referred to as boundary Construct 3D environmental model of facility positions. 100 115 130 2 9


10/15

Select set of component models and/or component types from Select positions within the 3D environmental model at which specific signal-to-interference ratio, specific throughput, etc.) metric (e.g., specific received signal strength coverage level, spaced positions within 3D environmental model to serve as a selection set of available component models and/or types model (e.g., 5 feet). System automatically selects equally-Select input signal characteristics (e.g., signal power) for a particular wireless communication system performance Specify whether to allow all possible configurations for Select precision of grid overlay onto 3D environmental is desired. Selected positions referred to as boundary selected component models and/or component types selected component models and/or component types Construct 3D environmental model of facility possible component placements. positions. 20 90 130 95


















14/15

7		7	, , ,	77	,		; ;=	- - - - - - - - - - - - - - - - - - -	٧ڔڹ	والم منه	g tel		. 5.	5, Y	ķić:	;		`,*\ \	28
HARIT		100															• "		
		Judg													_		_		
5	""一个	Z Aves Rotator	250.00 dea	50.00	30.00 dec	30.00 deg	230.00 deg	320.00 deg	88	310.00 deg	320.00 deg	330 00 den	290.00 deg	50.00 deg	330.00 deg	150.00 deg	320.00 deg	0.00 deg	
	7. Mark								м	ਲ⊲	⊬3 - रू	3 M	1 XI	ਲ	×	₽	æ	ö	
	1.000	A. Ho	0.00 deg	50.00 deg	0.00 deg	0.00 deg	0.00 deg		0.00 deg	00 deo		8 8	0.00 deg	80 690	8	50.00 deg	0.00	0.00 deg	語が記録
	W. Care	Ž.														!		ਡ.	
	大大	Std Dev. XAte Rotation YAte holder	210.00 deg	310.00 deg	250.00 deg	80.00 deg	90.00 deg	28.88 28.88 38.88 38.88 38.88 38.88	30.00 deg		888	140:00 dep	30.00 deg	270.00 deg	140.00 deg	310.00 deg	an moed	J.W. deg	
					-		.			•		· 9 8	••.		٠			_	到時
	U. Ch	PS	0.82	0.7548	0.75 gB	93.0 93.0	0.7	8 8	8 6	7.0	80	6.0	2	0.75 68 68	2 4	8 6	2 6	3	
100	3	X																	
1.00	Section 2	Section 1																: •	ų (E
Tare !			a	왕 ·	8.9	8 9	B 9	9 96	9 99	9	8	₩.!	8 9	В Ч	9 €	r 4	· 18	: : }.	Select Select
**	1	Magn.		8 S	3 8		8 8	900	9 90 0	800	000 B	000	8 8	8 8	8 8	900	800	-	Replace Curent anterna with sele
A.c. P. W.	1	9	3 8 3				1/0	3		_				02151		r			Culterit
7		2 42.5	i i				4/5 dea.	gp		olar Ana	į	Ę		Te &s 74			_		Replace
. ,		11991 2					E. S.	Se pag	_	lent 45 P			Z	Gain (sar		_	5 GB Garri		1/
		Z 2			. S	NWO	B dBd Ge	45) Polar	2 dB Gai	Jd Vert/S			Gen ON	16 dB	G G Gerr	3 dB Gar	deg 12.9	-	
	Description	d8 OWNI PCN 1860-1990 300 44- 3 00 - 2 0	30 den 10 dBd Gain	78 deo 10 mBd Gain	60 dec. 17 dB oain	7.5 dB Gan DMNI	65 deg. 16.8 dBd Gain PCS w/5 deg. D/T	Dual (Slant 45) Polarized 50-ohm 300W	83 deg. 15.2 dB Gain	OptiFili 11dBd Vert/Slant 45 Polar Anay	5 dbimaxgam	Sound in 13 and barn 870 MHz 6 de Gam OWN	Merk 10 dB Gen DMN	Scala 48 deg. 16 dB Gain (same as 740215)	105 deg. 9.5 dB Gain	92 deg. 11.3 dB Gam	1L-TEK 60 deg. 12.5 dB Gain	42	
	Ď	•	· 65	. ~	· 23	~	ន					3 6	ž	လွ	Ë	83	≓	*	
	*									PSSU-11-UU_M2									
	:	1920		0			-16-5		<u> </u>	Z .	- 0.80 - 0.80	5			916				
	Part #	ASPP2933 1920	7144.23	WA-8001	5963	1109	PCS A 065-16-5	ě	3878 HB	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	6050-14	740247	7080DS	16-875	SAL411 C4 R105	ALPSZIZN 11 pm on	A-803 60		
-	٩	¥	ĸ	Æ			:	お る	ទី ខ	2 5	: 8	Z	2	& :	•••		₫		
	8	fecom			Antenna Specialist		〈COMSAT-RSIMark グ	4	Toducts	בי בי בי					ć	K awateum Larparation 7 Till Tek		· <u>-</u>	,
	endechrer	Allen Telecon	Aligon	Antel	Antenna	Celwave	COMSA1		K vectoel Moducts X FMs Noveles	KGENERIC	Hazeline	X Kathrem	XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	Scale		SWGGGG	L		- 880X
Ŀ	ž	*	X	<u> </u>	*()	※ }	<u>*1</u>	۲Ņ	ΚŅ	€ })	K	米)	¥۵	ΚŅ	ťΩ	<u> </u>		1



